

AMERICAN INSTITUTE  
OF  
ARCHITECTS

JUN 27 1975


LIBRARY

# new mexico architecture

\$1.00

May-June 1975





*After 6 years  
research,  
A MAJOR TECHNICAL  
BREAKTHROUGH!  
A revolutionary  
new finish...*

**THE NEW**

***Spectra-Glaze*® II**

® Reg. U.S. Pat. Off., Canada and other countries by THE BURNS & RUSSELL CO.

**STRUCTURAL GLAZED MASONRY UNITS!**

**A SATIN FINISH that is  
EASY TO CLEAN...  
EASY TO KEEP CLEAN  
...RESISTS MARKING  
EASY FOR THE MASONS  
TO CLEAN DOWN...  
EXCELLENT COLOR CONSTANCY**

**Plus all the economic and structural advantages of traditional SPECTRA-GLAZE® Block . . . Permanent sanitary finish, thru-wall loadbearing units, fire ratings, accurate two-faced units, 48 colors, etc. . . . Helps meet your energy crisis problems, with excellent insulating advantages . . . and it's AVAILABLE!**

**Featherlite Corp.** announces a new Distributor for SPECTRA-GLAZE® II Block in northern New Mexico:

**REGO BLOCK COMPANY, INC.**





vol. 17 no. 3

IN THIS ISSUE

A letter to the editor is on page 9. It concerns the appointment of Stanley Hathaway, ex-governor of Wyoming, to be Secretary of the Interior. As we go to press it seems all too probable that our Senate will approve of Mr. Hathaway. Why, I cannot conceive, but then I too often find the Congress inconceivable. However, the letter is an important warning to us; we will have to keep a close, watchful eye on Mr. Hathaway.

□ □ □ □

Don't be misled by an ad in the Yellow Pages!

In the Santa Fe-Los Alamos telephone book released in March of this year is a totally misleading claim. In a large display advertisement on page 139 of the Yellow Pages, Richard M. Childers indicates that he is a member of certain organizations by inserting three sets of initials beneath his name. He thereby suggests that he is a corporate member of AID, the American Institute of Interior Designers, which he has never been, and a professional member of NSID, the National Society of Interior Designers, which he has never been. (Please see page 9 NMA, March-April 1975 which reports the merger of these two professional organizations into the American Society of Interior Designers, ASID).

Correspondence with the national headquarters of ASID advises me that no application for membership has been received from Mr. Childers.

I do not wish to imply that Mr. Childers is not capable in his chosen field. I only wish to point out to the readers of this magazine that to the best of my knowledge, Mr. Childers is not now, nor has he previously been, a member of AID, NSID, or ASID.

In the ad Mr. Childers also implies membership in SMDI; he may well be, but I do not know what is a SMDI. As President of the New Mexico Chapter of ASID, which encompasses all members of the former AID and NSID, and as editor of this magazine, which in the last issue published the roster of all current members of ASID, I feel that you the reader, should be informed of the advertisement; unfortunately, its deceptive message will be before all users of the Santa Fe-Los Alamos telephone book until March 1976.

So, watch out as your fingers go walking through the Yellow Pages.

—JPC

# nma

may-june 1975 • new mexico architecture

Editorial 9

Is Stanley Hathaway the  
right man for the job?  
A reader thinks not.

Solar Heating Sub-Systems—Part I 11

The Architects, Taos

Index to Advertisers 22

(Cover — Montezuma Hotel — Photographer — Robert Nugent)

—Official Publication of the New Mexico Society of Architects, A. I. A.—


Society Officers

President—Bob Campbell  
Vice President—Edwin French  
Secretary-Treasurer—George Owen  
Director—Bill Waters  
Director—Gene Hunt  
Director—Charles Nolan, Jr.  
Director—Wilbur Harris  
Director—Robert Strader  
Director—John Conron, FAIA/FASID

Commission for NMA

John P. Conron, FAIA, FASID—Editor  
Ronald K. Hill—Associate Editor  
Bainbridge Bunting—Editorial Consultant  
Robert G. Mallory—Advertising  
Mildred Brittle—Accounting  
and Circulation  
John W. McHugh  
Sam Pool






**Ponding causes a whole deluge of problems. Zonolite roof deck systems turn them off.**

Zonolite® has roof decks for everything. For the slope-to-drains. For hurricanes. For protection against fire. And for insulation.

Roof deck systems certified by Zonolite. Available everywhere in the U. S. and Canada. Installed by approved applicators each and every month of the year.

Just talk to your local Zonolite representative. He'll be pleased to consult with you and come up with a recommendation that will satisfy all your design requirements.

Want to correct a roof deck problem. Or better yet, prevent one in the first place? Say the word!



**ZONOLITE**

Southwest Vermiculite Co.  
5119 Edith Blvd. N.E.  
Albuquerque, New Mexico 87107



**CRUSHED LAVA CINDERS**

Screened to Proper Size For:

- Running Tracks
- Roofing Aggregate
- Decorative Ground Cover
- Rip-Rap
- Large Landscape Boulders



**ROCKY MOUNTAIN  
STONE COMPANY**

4741 PAN AMERICAN FREEWAY, N.E.  
ALBUQUERQUE 344-2611

**The paints and coatings  
Southwestern  
professionals use.**

Easy-on interior paints, climate-designed exterior paints, color coordinated wall-coverings, industrial-technical coatings, and a complete selection of professional supplies and accessories. Since 1936.

**Hanley  
Paint**  
Manufacturing Co.

Albuquerque, N.M.: 1214 San Pedro N.E.  
El Paso, Texas: 1531 Magoffin, 9054 Dyer,  
7636 Gateway East, 5937 N. Mesa



# FROM CONCEPT TO COMPLETION



Exclusive distributors for TAYLOR

**Consultation  
Planning  
Design  
Layout**

Criteria, skill, artistry and experience are fused to produce laboratory furniture meeting the most exacting requirements of contemporary science educators and architects. Units immediately available and within the reach of any school or institutional budget.

Architects use our design consultation services for:  
Science Labs / Offices / Artrooms / Dormitories /  
Libraries / Auditorium Seating / Home Economics  
Labs / Gymnasiums

**UNIVERSITY BOOK STORE  
ALLIED SUPPLY CO.**


2122 Central, SE  
Phone 243-1776  
Albuquerque, N. M.

## METAL STORE FIXTURES

*Beautiful . . . Functional*

AVAILABLE LOCALLY

*Display Flexibility*



**REEVE FLOOR-TO-CEILING MERCHANDISER** with glass shelves for new elevations in dramatic displays. Effectively used for back bays and area dividers. Tension poles are double slotted on two sides with internal adjustable spring action to maintain rigid tension. Unit can easily be moved to any location. **CLASSIC ISLANDER** with glass shelves to complement items on display. 30, 36 and 48 inch modules.

Exclusive New Mexico and West Texas distributor for full line of showcases, metal islands, wall units, shelves, peg board hooks, wire baskets, hang rod—in stock for immediate delivery.

See our showroom or write  
for free color catalog.



**CUSTOMCRAFT FIXTURES**

4914 Pan American Freeway, N. E.  
Albuquerque, New Mexico 87109  
505 881-9200

## YOU SAVE WITH NEW *Spectra-Glaze II* GLAZED BLOCK WALLS


**CONSTRUCTION** — Build and finish in one operation . . . walls go up faster — one trade, large units lay up fast . . . thru-wall load bearing units eliminate expense of back up wall.

**MAINTENANCE** — No refurbishing ever. Permanent, sanitary, factory finish — cannot peel or blister . . . easy to clean and keep clean.

**ENERGY** — Excellent U-factors with lightweight block and insulating granular fill.

**INSURANCE** — Maximum security and protection at lowest cost, with fire-rated walls.

**GOV'T REQUIREMENTS** — Meet USDA and OSHA specifications for health, sanitation and safety.



© U.S. Pat. Off., Can. & other countries by THE BURNS & RUSSELL CO.

FEATHERLITE BLOCK CO., Box 489, Lubbock, Tex. 79408, 806/763-8202  
FEATHERLITE BUILDING PRODUCTS CO., Box 9977, El Paso, Tex. 79990  
CREGO BLOCK COMPANY, INC., 6026 Second St. N.W., Albuquerque, N.M.  
505/344-3475

**YOU SAVE TIME / YOU SAVE MONEY**  
WITH THE ECONOMY OF BLOCK & THE PERFORMANCE OF GLAZE



# the *Broadway* and Prestressed Concrete

The Broadway Department store in Coronado Center in Albuquerque is now under construction using 8 foot twin tee prestressed concrete floor members totaling 115,600 square feet on two of the three floors. All columns and beams were also precast, prestressed concrete. Erection was accomplished in only four weeks working time.



ARCHITECT—  
ASSOCIATED ARCHITECTS  
& PLANNERS



CONTRACTOR—  
BRADBURY & STAMM  
CONSTRUCTION CO.



**PRESTRESSED**   
**CONCRETE PRODUCTS, INC.**

(505) 345-5671

1304 Menaul Blvd., N. E., Albuquerque, N. M. 87110



**Century Glazed**


**MISSION  
TILE**

*Classic, simple to install,  
fireproof, weatherproof, made  
of concrete, yet lighter than  
clay, stronger than clay at a  
fraction of the cost of clay.*

**Century roof tile, inc.**

2700 Second St., S. W.  
Albuquerque, New Mexico 87102





serving New Mexico  
and the El Paso area  
with

## Quality Concrete Masonry Products and many allied building materials



*Modernfold Wood and Plastic Folding Doors*  
*Hollow Metal Doors and Frames*      *Reinforcing and Fabricated Steel*  
*Steel and Formica Toilet Partitions*      *Commercial Hardware*  
*Commercial Toilet Accessories*      *Moderncote Vinyl Wall Covering*  
*Residential and Commercial Steel and Aluminum Windows*

### Builders Block & Stone Co., Inc.

P. O. Box 1633  
Roswell, N. M. 88201  
505 622-1321

### Builders Block & Supply Co., Inc.

P. O. Drawer FF  
Las Cruces, N. M. 88001  
505 524-3633

### Builders Block & Stone Co., Inc.

P. O. Box 10284  
Albuquerque, N. M. 87114  
505 265-6085

### Builders Block & Supply Co., Inc.




Telephone  
El Paso  
915 532-9695

Members: New Mexico Concrete Masonry Association, National Concrete Masonry Association



SPRAY INSULATION-  
ACOUSTICAL SYSTEM

for its . . .



**Keers, Inc.**

3323 STANFORD, N. E.  
ALBUQUERQUE, NEW MEXICO



# MR. PRESIDENT,

## HAVE YOU EVER THOUGHT ABOUT ASSIGNING OUR WILDLIFE REFUGES TO THE CIA?



Or maybe the Coast Guard? Or the Social Security Administration? You haven't? Of course not. But your Secretary of the Interior may have. In fact, he has already started along such a course; hereafter more than two million acres of national wildlife refuge system lands in the West—three wildlife ranges established for the protection and management of wildlife habitat by President Roosevelt in the 1930s—will be managed exclusively by—not the FBI or Export-Import Bank—but by an agency just as ill-chosen: the Bureau of Land Management.

Kicked out in the process is the U.S. Fish and Wildlife Service, the one agency that has a mandate to manage federal wildlife habitat.

Mr. President, already the Secretary has recommended that BLM be given primary jurisdiction over two critically important wildlife areas in Alaska—the huge Noatak National Arctic Range and the Iliamna National Resource Range. Is all this part of a plan to dismantle our national wildlife refuge system—a system that embraces more than 30 million acres in 49 states? Will the national parks be next? What's this we hear about BLM establishing a *Natural Park System* to compete with the National Park System?




The Bureau of Land Management! Can it be true? The very same Bureau of Land Management that has been so cozy with commodity interests these many years? The Bureau of Land Management that has condoned—even encouraged—reckless overgrazing of our public lands? That has been destroying wildlife habitat on these wildlife ranges against the pleading of the Fish and Wildlife Service for the past three decades? That had to admit last year that 83 percent of its administered grazing lands were in fair, poor or bad condition? That Bureau of Land Management?




Yes, that Bureau of Land Management. It's an outrage, Mr. President, and we ask you to overrule your Secretary of the Interior on this jurisdictional shift—*now*, before BLM can put its policies into effect.

What do the "wildlife experts" at BLM have in mind for the Kofa Game Range



in Arizona (660,000 acres), the Charles Sheldon Antelope Range in Nevada (578,000 acres) and the Charles M. Russell Wildlife Range in Montana (970,000 acres)? They say they will continue to manage the areas primarily for wildlife use, but they're employing a term never before used in connection with wildlife refuge management: *multiple use*. The intent is clear, as is BLM's record elsewhere—using chemical herbicides, fencing and bulldozer-chaining of shrubs like pinyon juniper, all to remove native plants on which wild animals browse and to replace them with grass, on which livestock graze.



How long will it be before wildlife becomes one of the *other uses*, one of the afterthoughts, in this vast domain that once existed primarily as a home for America's dwindling populations of threatened wildlife species?

Mr. President, this nation has precious little habitat left for animals and birds which depend on natural conditions for survival—for example, the desert bighorn sheep, bald and golden eagles, the endangered peregrine and prairie falcons. We have paved, stripped, plowed and denuded most of it, first in our westward expansion and more recently in our shift from farm to city, our urban sprawl and our Great Obsession with the automobile. Therefore, what little we have left needs to be protected and managed primarily for its wildlife values.

Mr. President, we know there are some fine public servants in BLM, but this is an agency that is constantly badgered by higher-ups in government—yes, even by the White House—in the name of heavy-handed commodity interests. Grazing and mineral interests thus get its major attention. To many of its policy makers through the years wildlife has been an uneconomic nuisance without much of a constituency.

For thirty years BLM has been a deterrent to sound wildlife management on the big wildlife ranges in the West. Yet the Fish and Wildlife Service was always there to act as a restraining influence on the excesses of BLM. Wisely, Fish and Wildlife was given exclusive jurisdiction of the Desert Wildlife Range in Nevada in 1966, and recently the same agency was given the same undivided jurisdiction over the Cabeza Prieta Game Range in Arizona. But where the commodity interests have made themselves heard, the Secretary of the Interior has elected to give exclusive jurisdiction to an agency that knows little about wildlife management and *couldn't care less*.

## THE WILDERNESS SOCIETY

1901 Pennsylvania Ave., NW  
Washington, DC 20006

*All of this is to be accomplished, Mr. President, without even lip service to the National Environmental Policy Act, which requires a study of environmental impact when major federal actions affecting the environment are to be undertaken. How can this be?*

Mr. President, the 100,000 members and contributors of The Wilderness Society call upon you to reverse your Secretary in this serious error. Now 40 years old, this organization has fought long and hard for the preservation of a significant portion of the remaining wilderness in this country—both for its importance to man and for the vital part it plays in sustaining wildlife populations. We believe it is vital that the public interest in the preservation of wildlife be placed higher on the scale of values than the short-term interest of a handful of western cattlemen and mining companies.



Please reverse the Secretary's decision and see that these wildlife ranges are assigned instead to the one agency that knows about wildlife and values its preservation—the U.S. Fish and Wildlife Service.

Since 1935 The Wilderness Society has been the principal citizen organization working for the preservation of the vestiges of our great American wilderness.

Ads like this cost money. You can help. Send tax-deductible contributions to The Wilderness Society Wildlife Fund, 1901 Pennsylvania Ave., N.W., Washington, D.C. 20006. We'll be glad to send you, in turn, a free pamphlet, "Wildlife Needs Wilderness."



*I received this letter from a concerned reader. Mrs. Untermyer maintained a home in Wyoming for several years before moving to Santa Fe.*

Editor, New Mexico Architecture:

Among the numerous ill-advised actions taken by President Gerald Ford the appointment of the ex-governor of Wyoming, Stanley Hathaway, as Secretary of the Interior will possibly have in the long run the most lasting effect on the life of America.

As governor, Stanley Hathaway was a self-described promoter of industrial logging and mining development in Wyoming. He went on record as favoring the damming of the scenic, recreation rich upper Green River, flooding private lands and fishing areas and advocating an absurd diversion of the water from needed agricultural use to electric power plant cooling; he urged increased lumbering and clear cutting of timber on slow recovery national forest areas; he backed increased sale and leasing of Wyoming public lands for coal mining and oil shale development without due safeguards and with quite small returns to the state, thus creating a bonanza for coal and oil interests.

In order to create more jobs Governor Hathaway asserted that the natural resources of the state should not be left unused, even if the process of using them had results which adversely affected not only Wyoming, but adjoining states as well. To implement his ideas he has stated, in so many words, that if ecological balances were disturbed, environmental safeguards lowered or swept aside (although he denied they would be), wilderness areas invaded and wildlife habitats threatened, it was more important to create jobs in the state. This has proven to be something of a boomerang. In the process of development of coal, Rock Springs, and oil and minerals, Gillette, two good-sized "boom" towns have been created. Both have major water, sewage, housing and school problems for which no prior preparation or planning was done; apart from the acute housing and other ills, this has resulted in greatly increased crime and mental illness figures.

In almost all respects Hathaway has urged haphazard development of resources regardless of environmental and social impact; he has demonstrated little or no understanding of the long range consequences. He has consistently, and quite often scornfully, resisted the efforts of informed conservation organizations to establish and preserve wilderness areas and to protect public lands from exploitation.

To be sure, jobs are needed. But careful, thoughtful planning can create jobs and, at the same time, respect the environment. Natural resources can be used, but must not be abused or destroyed. The generations to follow should be able to live, enjoy and derive benefit from the natural resources of Wy-

oming. Thoughtless planning and development of the Hathaway type will present our children with a vast, but desolate landscape.

The Department of Interior is a hodge-podge of often contradictory agencies. It includes the Bureau of Reclamation, which likes to build dams wherever it can find a stream and which has a strong lobby at the Congress to insure jobs for itself. There is the Bureau of Land Management which is presently engaged in an effort to take over management of three large national game reserves and to gain control of proposed Alaskan National Parks and Wildlife Ranges. The Bureau has pursued a policy of "multiple use." (*See ad., page 8, opposite*) In the past this policy usually has meant use by mineral and grazing interests which have no interest in nor concern for ecological values. Further, the Bureau has allowed for energy exploitation and unregulated recreational use. All of this "multiple use" has resulted in considerable erosion damage and overgrazing.


In contrast is the National Park Service, which also is under the Department of Interior. According to the National Park Act, the Service is entrusted with the protection and preservation of some of our outstanding, unique and most beautiful areas throughout the country, although it is given very little money with which to carry out this purpose. It is supposed to allow park access to people in a number consistent with the preservation of those features for which the park was established. Hathaway says, as have others, "Parks are for people," and of course they are, but in this connection he strongly advocated the building of a jetport in Jackson Hole, Wyoming, which would have invaded Grand Teton National Park even more extensively than the present airport, because it would enable more people to come in more easily. In the face of a very strongly worded adverse impact statement, Hathaway urged the airport extension with apparently no conception of the probable consequences. It is unfortunate, but a fact, that too many people at one time using the parks means destruction of the parks, so that the people who follow us in time will have no parks, or at best, badly damaged ones.

The Secretary of the Interior is confronted with difficult and often conflicting problems and pressures; a well balanced and above all, informed judgement would seem to be a pre-requisite for the job. The past record of Stanley Hathaway hardly indicates that he possesses or can exercise such judgement. Unless, while in office, he radically changes his past attitudes, we can anticipate a rape of our public resources as those in Wyoming were raped.

Elise S. Untermyer, Santa Fe, N.M.



Nothing we say about our tile  
can tell you as much as this photo.



Take another photo in 10 years  
and it'll be even more beautiful.

We could describe what goes into San Vallé genuine clay tile—the ingredients  
and the process—and explain how well it insulates and protects.  
But you choose a roofing material primarily on the basis of aesthetics. And that's where  
San Vallé tile's permanent beauty becomes a deciding factor.  
You wouldn't settle for a poor substitute. Would you?

**San Vallé** TILE  
KILN  
Since 18

1717 No. Highland Avenue, Los Angeles, California 90028 ■ (213) 464-72

Photo: Plaza de Oro, Encino, California • Architect: Ebbe Videricksen, A.I.A.

THE NATION'S LARGEST PRODUCER OF GENUINE CLAY ROOFING PRODUCT



# SOLAR ENERGY & HOUSING—Part I, CLIMATIC ANALYSIS

prepared by The Architects, Taos

The intent of this report is to investigate a broad technique of climate analysis which will facilitate the identification and evaluation of the *major* climatic parameters that affect building designs incorporating solar heating sub-systems, and to develop a graphical presentation of the analysis as it applies to the continental United States.

In searching the literature for data on the many variables which can affect design decisions in solar-heating applications, two of the most significant and obvious factors are:

1. The heating load on the building, as imposed on an hourly, daily, and long term basis.
2. The availability of solar energy, also as a function of short and long term time periods.

## HEATING LOAD

In regard to heating load, a well documented and ample supply of data has been recorded for most localities. Degree-day maps are available from the U. S. Weather Bureau, plotting heating loads both monthly and annually. Finer details, both tabulated and computerized, are also becoming available from numerous stations, allowing a daily or hourly analysis of those climatic factors such as temperature, wind, and dewpoint, which determine heating demand. Although interpolation of this data for locations between recording stations can sometimes be unreliable in cases where geographic factors such as mountains, deserts, and large areas of water or vegetation affect the local microclimate, in general the existing data is adequate for regionalized studies of this climatic factor in the U. S.

## SOLAR ENERGY—GEOGRAPHICAL

The characteristics of the solar energy available at different geographical locations which can be utilized to meet all or part of a building's heating demand is less well documented. About 100 stations in the U. S. and Canada record daily data such as % sunshine, cloud cover, and the daily total of combined direct and diffuse solar radiation. Among these stations, very few report data on solar input which separates the direct (shadow-casting) from the

diffuse (sky radiation) component of the total energy received.

## DIFFUSE RADIATION

Solar energy is transmitted to the earth as radiation. In traversing the earth's atmosphere the intensity of the direct rays becomes reduced in varying amounts through *absorption* by water vapor (and to a lesser extent by ozone and carbon dioxide), through *reflection* by dust and water droplets, and through *scattering* by air molecules. That part of the reflected and scattered radiation which reaches the earth is known as diffuse or sky radiation. On sunny days, the peak intensity of this radiation is in the blue portion of the spectrum and gives the sky its color. The total radiation reaching the surface of the earth is the sum of the direct and diffuse components.

## EXISTING MAPS—INADEQUACIES

The commonly available insolation (solar energy) maps are prepared for monthly averages, and reflect the average daily total radiation falling on a horizontal surface during the month. Although such data is of value in gaining a general sense of where the total inputs are either high or low, it does not address the important differences in mode of arrival of the energy (direct or diffuse) or the average amounts of the direct solar input which can be utilized by collectors tilted southward. Since the traditional instruments for solar energy measurement (pyrometers) are usually designed to be operated on a horizontal plane, all data is in reference to this ground plane, and therefore maps plotting the recorded solar information need rather elaborate transformations to become graphically indicative of actual energy collection potential.

Plate A (Page 12) illustrates typical geographic plotting of heating loads and solar input. Heating loads in degree days per month are shown as shaded zones which have been highly simplified for clarity in the vicinity of abrupt discontinuities in load, particularly in the mountainous regions of the West. Solar input, in monthly average of daily btu/sq. ft. on a *horizontal* surface, is illustrated by the heavy isolines, spaced at intervals of 200 btu/sq. ft./day.






Plate A

In the month of December, we can see that the average daily total insolation on a horizontal surface in portions of the State of Washington is only one-fifth as great as in most of New Mexico and Arizona. Detroit receives the same average inputs as the northern tip of California. The monthly average for New York City is about half of that for Central Florida. As expected, solar input is reduced with increasing latitude, yet the Western States appear to enjoy about 25% more input than areas of equivalent latitude east of the Mississippi.

Although this type of insolation data, overplotted on heating load averages, is of obvious usefulness to the designer of solar heating systems, the specific characteristics of solar collector geometry cannot be optimized from the inspection of this data alone.

#### MAXIMIZING DIFFUSE

As mentioned earlier, important differences exist in the mode of arrival of the solar inputs. Diffuse radiation is generally best received on a horizontal plane, since by definition its origins are always from the entire hemisphere of the sky, whether cloudy or

clear. Although the energy contribution of the diffuse component is substantially less than that of the direct component, its importance increases appreciably with the realization that it is often the *only* input during the coldest periods. Thus, if the relative percentage of wintertime diffuse is sufficiently high in a specific region, the plane of a solar collector may be oriented in favor of a horizontal position in order to achieve higher collection rates of *diffuse*. As a consequence of this low tilt angle, the ability of the collector to intercept *direct* winter sun would be reduced, because of the low altitudes of the winter sun. For example, the maximum solar altitude above the horizon at the winter solstice (December 22) varies, as a function of latitude, from a noon maximum of 20° in Minneapolis to 35° in El Paso.

Since information on solar input is presently available from most recording stations only in the form of *total* hourly and daily radiation received, a useful task is to illustrate a satisfactorily reliable method for estimating, at any given location, the separate percentages of the *diffuse* and *direct* components of solar input.

#### THE WORK OF LIU AND JORDAN

It is indeed fortunate that the literature contains invaluable and timely research on these and other aspects of solar radiation authored by Liu and Jordan in a series of papers published during the 1960's. Among other relationships developed in these co-authored works is a means of separating the *diffuse* and *direct* components at any given station when the *only* information available is the average *total* radiation received at the station. Although it is not appropriate in this report to retrace the ingenious process of development of these relationships, an interested reader is encouraged to refer to the *Solar Energy Journal*, July 1960, for detailed explanations of the following summary.

#### THE SOLAR CONSTANT

From experimental data, the intensity of solar energy arriving on a surface normal to the sun at the outer edge of the earth's atmosphere has been determined to average 442/btu hour/sq. ft., and this value is known as the Solar Constant. Seasonal variations of about 3½ percent occur due to eccentricity in the earth's orbit, and these variations can be accurately calculated, yielding a precise value for the intensity of this primary extra-atmospheric solar input at any given time of year.

#### THE SUNSHINE INDEX $K_t$

If, instead of being positioned at right angles to the sun's rays, an extra-atmospheric intercepting surface is parallel to the earth's surface above a given station, and therefore is tilted from the normal at






Fig. 1. Illustration of the theoretical extra-atmospheric surface on which  $H_0$  is calculated.

some angle (dependent on day of the year, time of day, and latitude of station) the resultant radiation intensity on the tilted surface will be reduced, and its value at any given angle of tilt can be calculated as a simple cosine function of the tilt angle. During any day, the sun's angle will continuously change in respect to a fixed intercepting surface, resulting in a corresponding change in energy input: zero at sunrise, increasing to maximum at solar noon, and subsiding back to zero at sunset. For a specific day, the total energy ( $H_0$ ) incident on the extra-atmospheric surface parallel to the earth's surface can be calculated by integration, using the value of the solar constant and a trigonometric description of the sun's apparent path across the sky. A station on the earth located below this extra-atmospheric surface can also record the total daily radiation ( $H$ ) falling on a horizontal plane at the station, and this data may be compared with the previously calculated amount of energy that would have fallen on the station if the atmosphere were not present. The comparison can be expressed either as a ratio, or (multiplying by 100), as a percentage of actual radiation received compared to the theoretical maximum falling on an atmosphereless station. This ratio of  $H/H_0$ , termed  $K_t$ , can be found for any place where pyrometers record the total daily or hourly solar energy.

Though Liu and Jordan refer to  $K_t$  as a "cloudiness index," actually the higher the fraction the lower is the actual cloud cover. The fraction is really an indication of the amount of total radiation that penetrates the atmosphere, and hence in this report  $K_t$  is referred to as the "sunshine index."

At those few stations equipped with instruments to record both diffuse ( $D$ ) and total radiation ( $H$ ) separately, another ratio,  $D/H$ , can also be obtained, and (multiplying by 100) may be expressed as the percentage of the daily diffuse radiation received compared to the daily total of both diffuse and direct.

By graphical analysis of recorded data from widely separated stations, Liu and Jordan discovered that a firm relationship exists between the ratio  $K_t$  and the ratio of  $D/H$ . A simplified graph of this relationship is illustrated in Figure 2. The highest plotted value of  $K_t$  (percent of the calculated "extra-atmospheric" that makes it through the sky to a recording pyrometer) is in the vicinity of 75%, which indicates that under total clear sky conditions, about 25% of the extra-atmospheric input is lost due to absorption or a return to space from scattering on the trip through the atmosphere. At this level of  $K_t$ , approximately 15% of the total energy received is contributed by the diffuse component.




Fig. 2. The ratio of  $D/H$ , the daily diffuse radiation to the daily total radiation, as a function of the sunshine index,  $K_t$ .

At the upper end of the curve, where  $K_t$  is about 5% of total extra-atmospheric input, the contribution from diffuse is 100%. No direct sun is seen on a day of this type, and the total cloud cover required for this condition is very dense—possibly 4 or 5 miles deep. All other points on the curve represent various degrees of cloudiness or other atmospheric obscuration, each point establishing a definite ratio of  $D/H$  for a corresponding value of  $K_t$ . It is important to note that these relationships are not for just a single station, and are not dependent on latitude or other factors peculiar to a particular location. They apply with impressive accuracy over a broad geographical range—Alaska, Wake Island, Helsinki, London, Nice, and to stations in the continental United States which record the  $D/H$  ratio. Using this graph, both the daily diffuse and direct solar components can be estimated from a single recorded observation—the total daily insolation ( $H$ ) received at any recording station.

Computations for any specific station and day are performed as follows:

1. Record  $H$ , the actual total energy received on a horizontal surface.
2. Compute  $H_0$ , the theoretical solar input for extra-atmospheric conditions.
3. Compute  $K_t$ , which is the ratio of  $H/H_0$ . Express as percentage if desired.



4. From the graph in Fig. 1, find the ratio  $D/H$  which corresponds to  $K_t$ .
5. Compute  $D$  by multiplying the  $D/H$  ratio by the value of  $H$  obtained in step #1.
6. If desired, the daily direction radiation ( $H_d$ ) may be found by subtracting  $D$  from  $H$ .

By this simple process the daily values of diffuse and direct may be established for any station which records the total daily solar radiation on a horizontal surface.

### MONTHLY AVERAGES

A similar process may be used to obtain *monthly* averages for the daily data. Daily records may be averaged to give the monthly average daily total ( $\bar{H}$ ), and the ratio  $\bar{H}/\bar{H}_0$  then produces a monthly average value for  $\bar{K}_t$ . Using a new graph from Liu and Jordan, Figure 3, the ratio of average daily diffuse ( $\bar{D}$ ) to average daily total ( $\bar{H}$ ) for the month is found as a function of  $\bar{K}_t$ , and this yields  $\bar{D}$  and the value of  $\bar{H}_d$  in the same manner as in the case of the daily calculations.




Fig. 3. The ratio of  $\bar{D}/\bar{H}$ , the monthly average daily diffuse radiation to the monthly average daily total radiation, as a function of the sunshine index,  $\bar{K}_t$ .

Due to the variations in cloudiness which always occur during a monthly period, the graph for the *monthly* average daily ratios is limited to a narrower range of values than is the graph for daily values. With two exceptions, the experimental values of  $\bar{K}_t \times 100$  for the U.S. fall within a range of 30 to 70. Seattle exceeds this limit at the cloudy end with a  $\bar{K}_t \times 100$  of 27. At the opposite end, Albuquerque scores the highest for stations recording  $\bar{H}$ , with a  $\bar{K}_t \times 100$  of 70.4%.

Having found a method for separating the monthly average daily diffuse and direct components, it is now possible to contemplate the preparation of maps which deal with each component separately. The data for diffuse on a horizontal surface is adequate as developed, since this component is most efficiently collected by a stationary *horizontal* collector. The direct, however, is preferably collected on a surface *normal* to the sun's rays, and except in the vicinity of the Equator, stationary flat plate

collectors are customarily *tilted* as required by latitude to optimize collection efficiency during the seasonal periods desired. Fixed collectors designed to favor the direct component during winter months are tilted at various angles southward from horizontal. One common tilt angle is equal to latitude plus 20 degrees.

### EFFECT OF COLLECTOR TILT




Fig. 4. Effect of tilting the collector to an angle of latitude plus 20° for all months of the year, illustrated for latitudes between 20° and 50°.  $R_d$  is the ratio of  $H_{ot}$ , daily radiation on a surface tilted southward from the horizontal to  $H_o$ , daily radiation on a horizontal surface, under extra-atmospheric conditions.

In order to compute the effect of such a tilt, the graph in Figure 4 was constructed from data developed by Liu and Jordan in 1967, and illustrates the ratio  $R_d$  as a function of latitude.  $R_d$  is the ratio of extra-atmospheric daily radiation on a surface tilted southward by an angle equal to latitude plus 20 degrees ( $H_{ot}$ ), to daily radiation on a horizontal surface ( $H_o$ ). The values of  $R_d \times 100$  indicate the percentage change in average daily direct energy incident on a collecting surface as a consequence of the latitude + 20° tilt. Note that this increase is especially dramatic at the higher latitude in the winter months. At 50° north latitude in January, a surface tilted at latitude + 20° receives almost four times as much direct energy as the same surface in a



horizontal plane. In Albuquerque in December, the increase is 2.3 times the horizontal. From the graph it is also apparent that during summer months the tilt will cause losses. For a full six month period, at 20° latitude the tilted surface will intercept less direct incident energy than if the surface were horizontal ( $R_d$  less than 1.0).

In developing the data to plot maps for December and January, the graph was used to convert the value of  $\bar{H}_d$  (monthly average daily direct radiation on a horizontal surface) to the average value of the same radiation on a south tilted surface ( $\bar{H}_{dt}$ ), for each of 74 stations in the U. S. A typical December

posting (below) for the first three stations provides interesting contrasts.

Note that although the measured radiation ( $\bar{H}$ ) for Albuquerque and Apalachicola is very close, the value of  $\bar{H}_{dt}$  develops a significant spread between these locations. Astoria receives only 28% of the  $\bar{H}$  of Albuquerque, and 27% of the  $\bar{H}_{dt}$ . These two stations approximate the limits of variation in solar input in the continental United States, with Albuquerque receiving about four times the total of direct and diffuse as Astoria. This large range has clear implications on the cost effectiveness of solar energy systems in the U. S.

Tilt = latitude + 20°

— = monthly average daily

Month = December


	Albuquerque, New Mexico	Apalachicola, Florida	Astoria, Oregon
North Latitude .....	35°03'	29°45'	46°12'
$\bar{H}$ (measured radiation) .....	1051.6	982.3	295.2 btu/sf/day
$K_t \times 100$ (% of extra-atmospheric) .....	70.4	54.3	33.2 percent
$\bar{D}/\bar{H} \times 100$ (% diffuse from graph) .....	21.0	34.0	53.0 percent
$\bar{D}$ (estimated diffuse $H \times D/H$ ) .....	220	334	157 btu/sf/day
$\bar{H}_d$ (direct on horizontal surface) .....	831	648	137 btu/sf/day
$R_d$ (tilt multiplier from graph) .....	2.32	1.94	3.66
$\bar{H}_{dt}$ (direct on tilted surface) .....	1927	1257	502 btu/sf/day
$\bar{D}/\bar{H}_{dt}$ (ratio, diffuse to tilted direct) .....	.115	.266	.314

Typical posting for first three stations in list of 74 used for plotting insolation maps. Values of  $H$  and  $K_t$  are from original Liu and Jordan calculations.

Continued Page 16 \*27

**Your  
business  
has to  
change with  
the times,  
so why  
have walls  
that won't?**

*New  
Mexico  
Office  
Furniture*



## Steelcase Movable Walls

A wall that's only a wall is an obstacle. But a Steelcase Movable Wall System can form an office today or a conference room tomorrow or two or three work-stations the day after. In other words, it gives you unlimited flexibility in planning your office interiors. And that's a boon to any business.

6437 LINN AVE. N.E. • ALBUQUERQUE, NEW MEXICO • (505) 265-7841






Plate B.

From data previously developed, it is now possible to compare geographic plots of  $\text{btu/s.f./day}$  of direct radiation on a tilted surface ( $\bar{H}_{dt}$ ) and  $\text{btu/s.f./day}$  of diffuse radiation on a horizontal surface ( $\bar{D}$ ) for the coldest months.

Examining the geographic behavior of  $\bar{H}_{dt}$ , we find severe alterations in the familiar isoline patterns typical to weather service plots of total daily radiation ( $\bar{H}$ ) as measured horizontally. The effect of collector tilt can dramatically alter those assessments of solar energy availability made from plots of  $\bar{H}$  alone. A surge of high input covers the Western States, with much of North Dakota and Montana ( $48^\circ$  lat.) receiving more direct insolation than Washington, D.C. ( $39^\circ$  lat.). An abrupt reduction occurs east of the states, bordering the Mississippi, deepening further into Ohio. The Northwest States are also very low, receiving only one-fourth of the input that falls into Arizona and New Mexico. California experiences an increase of 300% from its highest to its lowest latitudes.

In January, the December patterns intensify, with closely packed isolines running vertically through the midsection of the country. While the Western States

enjoy a higher daily average of sunshine, states east of the Mississippi are sun-starved even more than in December, despite the overall increase in extra-atmospheric ( $H_0$ ) in January.

It is perhaps well to note that there is nothing sacred about the tilt of "latitude  $+ 20^\circ$ ". Any fixed tilt is at best a compromise between summer and winter collection conditions and actually a tilt of "latitude  $+ 15^\circ$ " is more commonly recommended. Data provided by Liu and Jordan was given only for tilts equal to "latitude" and "latitude  $+ 20^\circ$ ". The latter was chosen for the maps in this report as it is judged to be the better of the two for winter collection of the direct component.




Plate C.

Plots of diffuse sky radiation appear primarily as quiescent functions of latitude. Except for the anomalous influences of the Western Mountains, the isolines are generally horizontal. From the Canadian Border the amount of diffuse more than doubles as the Gulf States are reached. From these maps, it seems that quantities of diffuse radiation as distributed geographically are NOT a significant function of cloudiness. Washington, D.C. does as well as Denver; murky Cleveland is close to Lander, Wyoming.







Plate D.

Although diffuse radiation ( $\bar{D}$ ) appears to be primarily a function of latitude, the severe variations in direct on a tilted surface ( $\bar{H}_{dt}$ ) which are weather-induced produce, in some areas, significant changes in the ratio of diffuse to direct. A geographic plot of this ratio,  $\bar{D}/\bar{H}_{dt}$ , reveals two regions in the United States where the diffuse component is of particular significance in collector selection and tilting. During December the middle Eastern States and those in the extreme northwest and portions of Northern California receive from 30 to 40 percent diffuse on a horizontal surface, compared to the input striking a tilted collector designed to optimize interception of the direct component. In these areas, all characterized by a low  $\bar{K}_t$  the diffuse component is of high significance, and a trade-off is called for in the determination of collector tilt, especially in consideration of the inherent reliability of diffuse, which often becomes the only available input during periods of high heating demand.

In the midwestern States, characterized by higher values of  $\bar{K}_t$ , the ratio of the diffuse component diminishes sufficiently in some regions so as to have only a marginal influence in optimizing the collector angle.

Plate E.

Using the direct insolation data for a tilted collector plotted on the previous plate, an over-plot of this data on a monthly degree-day demand map is useful in gaining a comparison of the available direct energy to the heating demand loads for the month. The solar inputs are in average btu per square foot per day, and the heating loads in degree days per month.

In general, the most cost effective applications for solar heating systems should occur in areas where solar insolation and heating demand are both high. Typical regions where this condition occurs are in the Dakotas, Montana and Wyoming, in the high altitude locations in southern regions of the Rocky Mountains, and in the mountainous sections of Southern California.

It should be noted that for clarity the map has been generalized, especially in regard to the degree-day zones. In areas of abrupt geographic changes, values of  $\bar{H}$  also change abruptly, resulting in possible severe local variations from average plotted values. In such locations, local microclimates must be investigated as a precondition to design decisions for solar heating systems.



# Fire containment specialist.



Call on the brick and block wall specialist to give your buildings added fire protection.

Drywall elevator shafts and stairwells can collapse in a fire. Steel loses its load-carrying capacity when temperatures rise above 1000°F.

Glass and metal curtain-walls can shatter or melt.

Brick and block walls won't burn, melt, buckle or disintegrate. No matter how hot the fire. Good reasons for masonry stairwells, masonry protective compartments, and masonry firewalls on every floor of your building.

No one can prevent all fires from starting, but the bricklayer, working with brick and block, can keep them from spreading.

Brick and block. Some of the best fire protection your building can get.



International Masonry Institute  
Suite 1001, 823 15th Street, N.W.  
Washington, D.C. 20005

Send me information on the fire safety advantages of brick and block.

Name \_\_\_\_\_  
Title \_\_\_\_\_  
Company \_\_\_\_\_  
Address \_\_\_\_\_  
City \_\_\_\_\_ State \_\_\_\_\_ Zip \_\_\_\_\_  
Nature of Business \_\_\_\_\_

## MASON CONTRACTORS ASSOCIATION OF NEW MEXICO






Plate F.

From data used on the previous plot of the  $\overline{H}_{dt}$  isolines, over-plotted on monthly degree day maps, a composite plot may be made, showing isolines of equal ratios of monthly direct insolation on a tilted surface to monthly degree day totals. In general terms, these isolines indicate equal monthly solar capability. Due to inadequate detail in the data available for plotting, the  $\overline{H}_{dt}$  lines are widened into bands. The number on each band is a ratio of average btu/s.f./day direct energy falling on a tilted surface to the number of average degree days per month.


Assuming a one month thermal storage capability for any given solar heating system, such a system could provide approximately the same percent of solar contribution to the transmission heating load of a building, using direct input only, at any point on a selected isoline.

Imagine a mobile dwelling of any size and appearance equipped with a solar-assisted heating system which utilizes a tilted collector and a one month storage capability. Suppose that, every year on December first, the dwelling is moved to a different location on a certain isoline of equal solar capability.

After several years of such hectic relocations, records should indicate that, regardless of location on the isoline, the average % of December heating requirement contributed by the solar system is constant. The smaller changes in average solar input caused by  $\overline{D}$ , the diffuse component which usually varies as a function of latitude, are not considered on these maps.


Another comparison of general solar performance, (using only the direct component) can be made. Suppose that the mobile dwelling has been stationed at various points on the (0.8) isoline, and has averaged, say, 40% of its heating energy for a given month from direct solar input. Then if the dwelling was relocated to any point on an isoline of double value (1.6), the % solar contribution should also double, in this instance reaching 80%. Thus, the ratio between the numbers on any two isolines is an indication of the relative monthly performance of identical buildings located anywhere on the considered lines.

Thermal demands which are not direct functions of degree-day loads, such as water heating, are not considered in the development of these solar capability charts.



This report was prepared by The Architects, Taos under sequential contracts with the AIA Research Corporation and Sandia Laboratories. It is expected that Part II of this report will be published in September/October issue of NMA.





Project: Continental National Bank  
El Paso, Texas  
Architect: B. Rea Nesmith  
Contractor: Arrow Construction Co.

"... WE SAVED A CONSIDERABLE AMOUNT OF MONEY IN COST OF MATERIAL AND LABOR."

Arrow Construction Company's E.D. Gunaca, said even more . . .

"We wish to take this opportunity to thank you for the professional way you handled our needs relating to our initial order for TRUS JOIST used in the construction of the Continental National Bank."

"You may also be glad to know that by using your TRUS JOIST system we saved a considerable amount of money in cost of material and labor since our own carpenters, on the job, were able to install same with ease."

"Finally, I wish to express our surprise and satisfaction in the prompt and punctual delivery of your TRUS JOIST to our job site, which contributed greatly to our efforts in meeting a very difficult completion date."

"We look forward to doing more business with you and TRUS JOIST in the future."

There's just nothing more we'd like to say.


Geo. B. McGill Co., Inc.  
3530 - C Pan American N.E.  
Albuquerque 87107  
Phone 505/345-4501



McGill - Stephens, Inc.  
4100 Rio Bravo St., Suite 320  
El Paso, Texas 79902  
Phone 915/544-4505

# Congoleum®

FINE FLOORS



# PEERLESS™

**CUSHIONED VINYL FLOORS.** THE ULTIMATE IN CUSTOM FLOORS FOR COMMERCIAL INSTALLATION. THE WHITE SHIELD BACK ALLOWS INSTALLATION ON OR BELOW GRADE.


ASK TO SEE THE WIDE SELECTION OF BEAUTIFUL PATTERNS IN PEERLESS CUSHIONED VINYL SHEET GOODS. EXTRA RUGGED, YET SO BEAUTIFUL.



125 DALE, S. E.  
P. O. BOX 2511, ALBUQUERQUE, NM 87125  
PHONE 877-5340

# Armstrong

MAKES WORK WORTH LIVING



Armstrong Soundsoak acoustical screens provide effective separation of work stations, while contributing substantially to acoustical and visual privacy. They are freestanding and easy to move. Covered with tufted nylon fabric in a choice of eight colors, Soundsoak screens are effective and decorative, especially when combined with Armstrong C60/30 ceiling systems.




FOR COMPLETE INFORMATION CALL:

**COOK'S BUILDING SPECIALTIES**

414 SECOND ST., S.W. 243-5541  
ALBUQUERQUE, NEW MEXICO • P.O. BOX 834, 87103





albuquerque little theater addition


george wynn, architect

## PERFORMANCE

Through-the-wall brick is the able partner to your unlimited imagination, combining beauty and structural capabilities in a masonry unit that does it all. See our representatives for more facts about our brick and the many ways it can perform for you.

## SUMMIT BRICK

5905 Marble, N.E. 268-9764  
Albuquerque, New Mexico



Artesanos offers you a fine selection of Saltillo Floor Tiles, and our colorful Talavera Tiles for any home redecorating.




Send for our free brochure.

**Artesanos Imports Co.**

222 Galisteo Street Phone 983-5563  
Santa Fe, New Mexico 87501

## One answer to the energy problem. The Natural Energy Home.




The Natural Energy Home makes the wisest use of our two main sources of household energy: Natural gas and electricity. Electricity is used for the things it does best. And gas is used for the jobs it does so well.

When gas is used directly for the big jobs like heating, cooking, water heating and clothes drying, 93% of its original energy is delivered to the home.

But to produce electricity to do those same jobs, a power plant must first burn natural gas, oil or coal. So by the time it's converted to electricity and transmitted to the home, *over two-thirds of the original energy is lost.*

When you're buying a new home, choose the one that saves money and conserves our precious energy. Look for the Natural Energy Home sign.

If you want the job done right...  do it with gas.

**SOUTHERN UNION GAS COMPANY**



# FLEX SHIELD


*waterproof flexible texture coating*

used on the exterior of the new

**J. Korber & Co. Building**

**2400 Menaul Blvd., Albuquerque**

Architect: Stevens, Mallory, Pearl & Campbell  
Painting Contractor: Keers, Inc.



Heavy texture coating for virtually all types of exterior and interior surfaces. Durable, waterproof, flexible.

## Wellborn PAINT

Mfg. Company, Albuquerque, N.M. 877-5050

*new mexico architecture*

**nma**


Published bi-monthly by New Mexico Society of Architects, American Institute of Architects, a non-profit organization.

**Editorial Policy:** Opinions expressed in all signed articles are those of the author and do not necessarily represent the official position of the publishing organization.

Editorial Correspondence should be addressed to John P. Conron, Box 935, Santa Fe, N.M. 87501. 505 983-6948.

Advertising: Send requests for rates and information to New Mexico Architecture, Robert G. Mallory, 115 Amherst Drive S.E., Albuquerque, N. M. 87106. 505 255-8668.

**Integrity and Beauty:**  
**The concrete facts of Southwestern life.**



Physics Laboratories and Lecture Hall on the University of New Mexico Campus  
Architect: Pacheco and Graham  
Structural Engineer: Robert Krause  
ChemComp Concrete supplied by Springer Corp.

When you want minimized shrinkage cracking for absolute structural integrity, durability and beauty, the concrete answer is ChemComp, Southwestern Portland's expansive cement. Check ChemComp's many advantages by writing for our free brochure: Box 392, El Paso, Texas 79943.



**SOUTHWESTERN PORTLAND CEMENT COMPANY**  
MAKERS OF EL TORO CEMENTS / EL PASO, AMARILLO, ODESSA

PRINTED BY

HALL-POORBAUGH PRESS, ROSWELL, N. M.

**INDEX OF FIRMS** who make possible the publication of NMA and the page upon which their message may be found:

Albuquerque Testing Laboratory .....	23
Artesanos Imports Co. ....	21
Builders Block & Stone Co., Inc. ....	7
Century Roof Tile, Inc. ....	6
Cook's Building Specialties .....	20
Crego Block Co., Inc. ....	2
Customcraft Fixtures .....	5
Design Interiors .....	23
William W. Douglass, Inc. ....	23
Hanley Paint Mfg. Co., Inc. ....	4
Hydro Conduit Corporation .....	24
Keers, Inc. ....	7
Mason Contractors Assn. of N.M. ....	18
McGill Co., Inc., Geo. B. ....	23
McGill Trus Joist .....	20
New Mexico Office Furniture .....	19
Prestressed Concrete Products, Inc. ....	6
Rocky Mountain Stone Co. ....	4
San Vallé Tile Kilns .....	10
Southern Union Gas Co. ....	21
Southwestern Portland Cement Co. ....	22
Southwest Vermiculite Co. ....	4
Spectra-Glaze .....	5
Stryco Sales, Inc. ....	20
Summit Pressed Brick & Tile Co. ....	21
University Bookstore .....	5
Wellborn Paint Mfg. Co. ....	22



# PLASTECO SKYLIGHTS

RESIDENTIAL, COMMERCIAL  
& CUSTOM — SEE SWEET'S 7.8/PL

Now represented in New Mexico by  
William W. Douglass, Inc.  
Albuquerque, N.M. 87109  
294-5326

## ALBUQUERQUE TESTING LABORATORY

Sub-soil Investigations  
For Structural and Dam Foundations


**Two Drills and Crews now  
available for Prompt Service**

Laboratory Analysis and  
Evaluation of Construction Materials

**All work done under the supervision  
of Registered Professional Engineers**

532 Jefferson St. N.E. — P. O. Box 4101  
Phone AL 5-8916 Albuquerque  
Phone AL 5-1322 New Mexico

## KALWALL® SYSTEMS FOR ENERGY SAVING BUILDINGS!



Kalwall is a complete, translucent, insulating wall

— or roof — system!

Kalwall lets you save heating and air conditioning energy — and use the sun's energy to even greater advantage to save on artificial lighting, and even pick up solar heat in the cold months! (Inquire about our New Sunwall!)

You can design your buildings with a choice of key ENERGY SAVING factors:

- It can have a variety of "U" Factors ranging between .06 and .40! \*

- It can have a light transmission value ranging between 3% and 85%!
- It can have Shading Coefficients from .85 to less than .06!

And Kalwall can be engineered for every building situation, every location, and every exposure!

PLUS — Kalwall buildings win design awards every year!

Write or phone Mr. Bruce Keller, Vice President, for complete information.

\* As much as 86%  
energy savings over  
single glass!

**Geo. B. McGill Co., Inc.**  
3530 - C Pan American N.E.  
Albuquerque 87107  
Phone 505/345-4501

**McGill - Stephens, Inc.**  
4100 Rio Bravo St., Suite 320  
El Paso, Texas 79902  
Phone 915/544-4505

## WHAT IS CFC AND HOW CAN IT HELP YOU?

AIA and CFC have formed the "Committee on Interior Environment" to provide a better working relationship between architect, furniture dealer and client. As your local contract dealer, we are pleased to announce our affiliation with the CFC as another means to improve the quality of service to the architectural community.

A Member of



"Professional Interior  
Furnishings Contractor"



**DESIGN INTERIORS**

COMMERCIAL & CONTRACT INTERIOR FURNISHINGS  
4121 PROSPECT AVENUE N.E. ALBUQUERQUE, NEW MEXICO 87110




Library  
American Institute of Architects  
1735 New York Avenue NW  
Washington, D. C. 20006 AB

Bulk Rate  
U. S. Postage  
**PAID**  
Roswell, N. M.  
Permit No. 47

Vol. 17, No. 3

## the TOTAL PRECAST CONCRETE BUILDING



Maximum Security and  
Future Expansion Capability  
Were Required. . . .


Precast Concrete  
Was the Answer!

The new Rio Grande Jewelers Supply Building in Albuquerque is truly an all concrete structure featuring precast concrete wall panels, precast fascia, precast exposed aggregate accent panels and prestressed concrete double tee roof.

Both requirements of maximum security and future expansion capability were met with a pleasing architectural design.

ARCHITECT—  
ROBERT F. ARMSTRONG

CONTRACTOR—  
COLTON CONSTRUCTION CO.



**HYDRO CONDUIT CORPORATION**

2800 SECOND ST., SW • ALBUQUERQUE, NEW MEXICO 87103